

FUJIAN EPOS ELECTRIC MACHINERY CO., LTD

EMEAN
POWER

WEICHAI
潍柴

ENGINE MODEL: WP10D200E200

EMEAN POWER


www.emeanpower.com
Email: sale5@fjepos.com
Phone: +86 19890349907

WHATSAPP



WECHAT




	机型: WP10D200E200 Model:	日期: 2021/2 Date:
	柴油发动机数据单 Diesel Datasheet	页码: 1 / 6 Page:

转速 Speed	发动机功率 Gross Engine Output		
	持续功率 kW COP kW	常用功率 kW PRP kW	备用功率 kW ESP kW
1500r/min	/	182	200

功率定义解释 Ratings definitions :


功率分类 Ratings Definitions	运行条件 Operating condition
持续功率 COP	1、每年运行时间不限； Unlimited using time per year; 2、在恒定的 100%负荷下运行； Continuous power is the maximum power available at a constant load factor; 3、不具备超负荷能力。 No overload capability is allowed.
常用功率 PRP	1、每年运行时间不限； Unlimited using time per year; 2、运行24h上平均负荷率不能超过70%； The average load rate is no more than 70% over 24 hours; 3、每 12h 内，可超负荷 10%运行 1h。 Overloading 10% for 1h within 12 hours of operation is allowed.
备用功率 ESP	1、每年运行时间不超过200h; The annual operating time shall not exceed 200h; 2、运行24h以上，平均负荷率不超过70%； The average load rate shall not exceed 70% over24h operation cycle; 3、不具备超负荷能力; No overload capability is allowed; 4、柴油机启动加速按照 Q/WCG136.13 进行，没有热机过程，由启动加速到标定转速需在 10s 内完成。自然吸气柴油机，环境温度在 5℃以下时，需增加预热设施保证柴油机出水温度在 30℃以上；环境温度 5℃以上时，无需预热设施。增压柴油机环境温度 10℃以下时，需增加预热设施保证柴油机出水温度在 30℃以上；环境温度 10℃以上时，无预热设

	机型: WP10D200E200 Model:	日期: 2021/2 Date:
	柴油发动机数据单 Diesel Datasheet	页码: 2 / 6 Page:

	<p>施。</p> <p>The acceleration of starting of diesel engines are carried out in accordance with Q/WCG136.13, and there' s no engine process. From acceleration of starting to calibration speed shall be completed within 10s. Natural aspirated diesel engine, when the environment temperature is below 5°C , need to increase preheat facilities to ensure that diesel engine water temperature above 30 °C. When environment temperature over 5°C, no preheating facilities are required.</p> <p>Supercharged diesel engine, when the environment temperature is below 10°C, need to increase preheat facilities to ensure that diesel engine water temperature above 30°C. When environment temperature over 10°C, no preheating facilities are required.</p>
备注 Descriptions	<p>1) 所有功率基于标准 ISO 8528-1, ISO 3046, DIN6271 , 误差范围±5%。 All ratings are based on operating conditions under ISO 8528-1,ISO 3046, DIN6271. Performance tolerance of ±5%.</p> <p>2) 测试条件：大气压力 100kPa , 25°C , 相对湿度 30% , 燃油密度 0.84kg/L ; 其他环境条件下可能需要进行功率修正 , 详情请与厂家联系。 Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%, with fuel density 0.84 kg/L. Derating may be required for conditions outside these; please contact the factory for details.</p> <p>3) 所有的数据均基于发动机带燃油系统、水泵、机油泵时获得的 , 而不带有交流发电机、风扇、其它选用设备和被驱动的附件。 Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump, without battery charging alternator, fan and optional equipment.</p>

基础数据 Essential Data

发动机类型 Engine model 柴油机 Diesel Engine
 气缸/气门数量 N° of Cylinders / Valves 6/12
 气缸分布型式 Cylinders arrangement..... 直列 In-line
 缸径×行程 (mm) Bore x Stroke (mm) 126×130
 排量(L) Displacement(L) 9.726
 燃油系统型式 Fuel System 机械泵 mechanical pump

	机型: WP10D200E200 Model:	日期: 2021/2 Date:
	柴油发动机数据单 Diesel Datasheet	页码: 3 / 6 Page:

进气形式 Aspiration	增压中冷 Turbocharged and aftercooled
压缩比 Compression ratio	17
飞轮壳尺寸 Flywheel housing	SAE1
飞轮尺寸 Flywheel	11.5' /14'
飞轮齿圈齿数 N° of teeth on flywheel ring gear	136
飞轮转动惯量 (kg/m ²) Inertia of flywheel (kg/m ²)	0.95
曲轴转动惯量 (kg/m ²) Inertia of crankshaft (kg/m ²)	0.35
排放阶段 Emission standard	无排放 Non
发动机尺寸(长×宽×高) (mm) Overall Dimensions with radiator (L x W x H) (mm)	1525×730×1063 (以外形图为准 The outer chart shall prevail)
发动机干重 (kg) Engine dry weight (kg)	875
不带辅助启动装置时最低冷启动温度 (°C) Min.cold start temperature without auxiliary starting device(°C)	-10
带辅助启动装置时最低冷启动温度 (°C) Min. cold start temperature with auxiliary starting device (°C)	-30
包装尺寸 Packing measurement (mm)	1873×974×1300
运输重量 Transport weight (kg)	980

进气系统 Air intake system


在涡轮增压器前允许的最大的进气温升(°C) Air intake temperature rise (°C)	/
清洁滤芯进气阻力 (kPa) Air intake restriction clean filter (kPa)	≤3.5
脏滤芯进气阻力 (kPa) Air intake restriction dirty filter (kPa)	≤7
额定工况下进气流量 (kg/h) Recommended air flow @ PRP (kg/h)	955
应急备用工况下进气流量 (kg/h) Recommended air flow @ ESP (kg/h)	1025
推荐最小进气管直径(mm) Min. diameter of intake pipe (mm)	100

中冷系统 Intercooling system

25°C环境温度下的最高进气温度 (°C) Max. intake temperature @ 25°C ambient temperature (°C).	55
进气温度与环境温度的最大温差 (°C) Max. difference between intake temperature and ambient temperature (°C)	≤30
中冷器允许的最大压力降 (kPa) Max. intake pressure drop of intercooler (kPa)	12

冷却系统 Cooling system

发动机允许的最高使用环境温度 (°C) System designed for ambient temperature up to (°C)	50
进出水外部管路的最小内径 (mm) Min. inside diameter of coolant outlet pipe (mm)	45

	机型: WP10D200E200 Model:	日期: 2021/2 Date:
	柴油发动机数据单 Diesel Datasheet	页码: 4 / 6 Page:

出水管报警温度 (°C) Coolant alarm (shutdown) temperature (°C).....	98
节温器初开/全开温度 (°C) Thermostat opening temperature/full open temperature (°C).....	71/82
冷却系统内最小保持压力 (kPa) Min. pressure in cooling system (kPa).....	50
发动机本身冷却液容量 (L) Coolant capacity of the engine (L).....	22

排气系统 Exhaust system

允许最大排气背压 (kPa) Max. exhaust back pressure (kPa).....	6±0.5
最大的排气温度 (涡轮前) (°C) Max. exhaust temperature before turbocharger (°C).....	≤700
最大的排气温度 (涡轮后) (°C) Max. exhaust temperature after turbocharger (°C).....	≤600
额定工况下排气流量 (kg/h) Exhaust flow @ PRP (kg/h).....	994
应急备用工况下排气流量 (kg/h) Exhaust flow @ ESP (kg/h).....	1031
推荐排气管最小直径 (mm) Min. diameter of exhaust pipe (mm).....	100
涡轮增压器法兰处允许的最大弯矩 (Nm) Max. bending moment of exhaust gas exit flange (Nm).....	10

润滑系统 Lubrication system

油底壳机油最小/最大容量 (L) Oil capacity Low / High (L).....	24
怠速时机油压力 (kPa) Oil pressure in normal condition idle speed (kPa).....	100-250
在额定转速下的机油压力 (kPa) Oil pressure in normal condition at rated speed.....	330-550
机油低报警压力 (kPa) Lowest oil pressure alarm (kPa).....	80
机油低停机压力 (kPa) Lowest oil pressure shutdown (kPa).....	80
机油最高温度 (°C) Max. oil temperature (°C).....	85-105
机油流量 (L/min) Oil flow (L/min).....	118
机油燃油消耗比 Oil fuel consumption ratio based on engine fuel consumption data.....	≤0.2%


噪声 Noise

发动机噪声 (声功率级) (dB(A)) Diesel engine noise (Acoustic power level) (dB(A)).....	100.1
--	-------

燃油系统 Fuel system

喷油泵进油口最大进油阻力 (kPa) Max. restriction at fuel pump inlet (kPa).....	18
喷油泵最大回油阻力 (kPa) Max. fuel return restriction (kPa).....	22
燃油最高进油温度 (°C) Max. fuel inlet temperature (°C).....	50
供油流量 (kg/h) Fuel supply flow (kg/h).....	38.93 ~ 35.35
输油泵最小压力 (kPa) Min. pressure of fuel pump (kPa).....	35
燃油进油管最小直径 (mm) Min. diameter of inlet pipe (mm).....	12
燃油回油管最小直径 (mm) Min. diameter of return pipe (mm).....	12


电器系统 Electrical system

	机型: WP10D200E200 Model:	日期: 2021/2 Date:
	柴油发动机数据单 Diesel Datasheet	页码: 5 / 6 Page:

电气系统电压 (负极接地) (V) Electrical system voltage (negative to ground) (V)	24
起动机功率(kW) Starter power (kW)	5.4
充电发电机额定电流 (A) Battery charger current (A).....	55
启动回路最大电阻 (mΩ) Max. electric resistance of starting circuit (mΩ).....	4
启动回路导线最小截面积(mm ²) Min. sectional area of wire (mm ²)	50
加热格栅工作电压(V)/电流(A) Heat The Grille Voltage(V)/Current(A)	/

热平衡测试数据 (环境温度 42°C)Heat balance test data (42°C)

发动机进/出水压力 Coolant inlet/ output pressure (kPa)	额定工况 Rated working condition	5.9/16.1
	超负荷工况 Overload working condition	5.5/16.2
冷却液流量 Coolant flow (m ³ /h)	额定工况 Rated working condition	14.1
	超负荷工况 Overload working condition	14.1
发动机进/出水温度 Coolant inlet/output temperature (°C)	额定工况 Rated working condition	72.2/76.9
	超负荷工况 Overload working condition	74.2/79.2
中冷器前/后温度 Intercooler inlet/output temperature (°C)	额定工况 Rated working condition	121.0/51.3
	超负荷工况 Overload working condition	131.0/52.2
中冷器前/后压力 Intercooler inlet/output pressure (kPa)	额定工况 Rated working condition	98.7/97.5
	超负荷工况 Overload working condition	113.2/111.9
发动机总热量 Engine total heat (kJ/s)	额定工况 Rated working condition	412.4
	超负荷工况 Overload working condition	452.9
中冷器散热量 Intercooler heat dissipating capacity (kJ/s)	额定工况 Rated working condition	17.2
	超负荷工况 Overload working condition	20.9
排气带走的热量 The heat taken away by the exhaust (kJ/s)	额定工况 Rated working condition	122.1
	超负荷工况 Overload working condition	135.0
冷却液带走的热量 Rated working condition	额定工况 Rated working condition	76.3

	机型: WP10D200E200 Model:	日期: 2021/2 Date:
	柴油发动机数据单 Diesel Datasheet	页码: 6 / 6 Page:

The heat taken away by the coolant (kJ/s)	超负荷工况 Overload working condition	81.2
发动机表面辐射热量 Radiation heat of the engine surface (kJ/s)	额定工况 Rated working condition	/
	超负荷工况 Overload working condition	/
注：因测量等误差原因，表面辐射热量按发动机总热量的 5% 计算。 Note: Because of test errors and other reasons, the surface radiation heat is 5% of the engine total heat.		

性能数据 Performance data

活塞平均速度 (m/s) Mean Piston Speed (m/s)	6.5
平均有效压力 (MPa)BMEP (MPa)	1.5
最高爆发压力(MPa) Maximum Burst Pressure(MPa)	/
最低空载稳定转速(r/min) Minimum No-load Speed(r/min).....	600-700
发火次序 Ignition Order	1-5-3-6-2-4
旋转方向 Sense of Rotation	逆时针 (面对飞轮) Anticlockwise (In the Face of Flywheel)

备注：所有参数如有更改，恕不另行通知。

Remark: All Parameters If Changed Without Prior Notice.