

FUJIAN EPOS ELECTRIC MACHINERY CO., LTD

EMEAN
— POWER —

ISUZU

ENGINE MODEL: JE493ZLDB-01

EMEAN POWER

www.emeanpower.com

Email: sale5@fjepos.com

Phone: +86 19890349907

WHATSAPP



WECHAT



型号 Model

JE493ZLDB-01



型式 Type	直列、四冲程、水冷、直喷式 燃烧室、机械调速 Water cooling, in line, four- stroke, wet liner and direct injection machinery
------------	---

缸数 Number of cylinders	4
---------------------------	---

缸径×行程 Bore×Stroke	93×102 mm
----------------------	-----------

进气方式 Aspiration	中冷增压 intercooling turbo
--------------------	----------------------------

活塞总排量 Displacement	2.771 L
-----------------------	---------

压缩比 Compression ratio	18.2:1
--------------------------	--------

工作顺序 Fring order	1-3-4-2
---------------------	---------

额定功率 Rated output	46KW
----------------------	------

备用功率 Standby power	51KW
-----------------------	------

标定转速 Rated speed	1800r/min
---------------------	-----------

最低燃油消耗率 Fuel consumption rate	≤210g/kW.h
----------------------------------	------------

外形尺寸(长×宽×高) Overall dimension	860×610×830mm
----------------------------------	---------------

质量 Net mass	245kg
----------------	-------

稳定调速率 Steady speed adjusting ratio at rated condition	机械调速≤5% machinery≤5%
---	-------------------------

润滑方式 Lubricating method	压力润滑与飞溅润滑复合式 Pressure lubrication and splash
----------------------------	---

起动方式 Starting method	电起动 Electric motor start
-------------------------	-----------------------------

曲轴转向 Crankshaft rotating direction	顺时针方向 Clockwise
--	--------------------

机油容量 Oil sump capacity	5.6 L
---------------------------	-------

机油牌号 Oil	≥API CF-4
-------------	-----------

机油压力 Oil pressure	0.1—0.50 MPa
----------------------	--------------

噪音 Noise	≤93dB(A)
-------------	----------

标定功率烟度 Rated output FSN	<3.0
----------------------------	------

排气温度 Exhaust	<500℃
-----------------	-------

机油温度 Oil temperature	<110℃
-------------------------	-------

冷却液温度 Coolingwater temperature	85±10℃
--------------------------------------	--------

发电机 Generator	14V/50A
------------------	---------

起动机 Starting motor	12V/2.8kW
-----------------------	-----------

注：技术参数系在标准环境（大气压力：100Kpa、进气温度 298K、干空气压 99Kpa、水蒸汽分压 1Kpa、相对湿度 30%）状况下的值。

Note: The parameters listed are values in standard environment (atmospheric pressure: 100Kpa, inlet temperature: 298K, dry air pressure: 99Kpa, partial pressure of water vapor: 1Kpa, relative humidity: 30%).

EMEAN POWER

www.emeanpower.com
Email: sale5@fjepos.com
Phone: +86 19890349907

WHATSAPP



WECHAT

