

EM10000

Gasoline Generator



TECHNICALS SPECIFICATIONS

Model:

EM10000

Gen set composed of engine and alternator perfectly assembled and fitted in a practical tubular chassis, that is adding great strength and versatility.



Genset General Characteristics

Prime Power:	50HZ/8KW	60HZ/8.5KW
Standby power:	50HZ/8.5KW	60HZ/9KW
DC Output:	12V-8.3A	
Voltage:	110V/220V, 115V/230V, 120V/240V, 127V/220V, 220V/380V, 230/400V, 240V/415V	
Fuel Tank Capacity:	25L	
Fuel Consumption:	≤2.85L/h / ≤3.0L/h	
Noise Level at 7M:	70~72dB(A)	
Product Dimensions:	675*525*540 MM	
Packing Dimension	690*540*560 MM	
N.W/G.W:	86KG/91KG	

OPTIONS

- Electric Start
- Digital Meter
- Socket Style
- ATS
- Handles & Wheels



Engine

Model:	194F
Fuel:	Gasoline
Cooling System:	Air
Type:	V-twin/L-single, 4-cycle
Bore x Stroke:	94*66MM
Displacement:	0.453L
Compression Ratio:	20:01
Engine Speed:	50HZ/3000RPM 60HZ/3600RPM
Rated Output:	50HZ/9.5KW 60HZ/10.3KW
Combustion System:	Crystal Ignition
Starting System:	Recoil Start / Electric Start
Lube Oil Capacity:	1.15L
Lubrication Oil:	CD Grade Or Higher (SAE10W/30/SAE15W/40)

Alternator

Type:	Self Excitation, Constant Voltage, Field Rotating, 2 Pole
Phase:	Single Phase/3-Phase
Power Factor:	cOsp 1.0/0.8
Insulation:	H
Portection Degree:	IP21

EMEAN POWER

www.emeanpower.com
Email: sale5@fjepos.com
Phone: +86 19890349907

WHATSAPP



WECHAT

