

# EM-W1100

## WEICHAI Engine

EMEAN  
POWER



### Generator Specification

| Service              | PRP          | ESP  |
|----------------------|--------------|------|
| Power (kva)          | 1000         | 1100 |
| Power (kw)           | 800          | 880  |
| Rated speed ( r.p.m) | 1500         |      |
| Rated Power factor   | 0.8 @lagging |      |

### Performance

|                         |                     |
|-------------------------|---------------------|
| Engine Brand            | WEICHAI             |
| Engine model            | 12M26D968E200/880KW |
| Alternator              | VG-404E/800KW       |
| Breaker                 | CHNIT MCCB 3P       |
| Control system          | AMF digital panel   |
| Fuel consum. @100% load | 195.7 g/kW.h        |

### CERTIFICATE:

EMEAN Power gensets are compliant with ISO 9001 and CE standard, which include the following directives: EN ISO 12100:2010, EN ISO 8528-13:2016, EN 60204-1:2006+A1:2009+AC:2010, EN 55012:2007+A1:2009




### POWER DEFINITION:

PRP(Prime Power): Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP(Standby Power):The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1.Overload is not allowed



# Dimension

| Type       | Open   | Silent |
|------------|--------|--------|
| Length (L) | 4650mm |        |
| Width (W)  | 2010mm | 20GP   |
| Height (H) | 2320mm |        |
| Net Weight | 7600kg | 9500kg |



## Standard Features:

- 1.power by Brand new water cooled diesel engine
- 2.Brushless alternators (Class H, with AVR)
- 3.Working condition: 0°C~+40°C (Antifreeze system needed if below 0°C)
- 4.Base frame fuel tank for continue 8-10hrs running
- 5.Digital control panel with auto protection
- 6.MCCB air circuit breaker for over current shutdown
- 7.Industrial silencer for silent type generator sets
- 8.Humanized design, simple operation, easy maintenance
- 9.Ventilation parts are designed with modular principles
- 10.Soundproof canopy which lined with sound reducing foam
- 11.All metal canopy parts are painted by powder foam
- 12.Glass Panel window
- 13.Lockable doors on front and back side for easy maintenance
- 14.Easy maintenance and operation
- 15.Easy lifting and moving, there is forklift hooks and crane holes on chassis
- 16.External emergency stop button
- 17.Steel chassis and anti-vibration pads
- 18.Includes diesel level sensor information to the controller




## Warranty

We shall provide a warranty of 12 months or 1200 hours from B/L date (whichever comes first), covering all manufacturing defects. We replace damaged parts caused by manufacturing faults or defected parts/materials, but exclude the damageable parts due to customer's incorrect man-made operation. After expiration, we still provides technical and spare parts support with cost for maintenance.

## WEICHAI 12M26D968E200/880KW

Please download the detailed engine data sheet



## Alternator VG-404E/800KW

Please download the detailed alternator data sheet



## Digital control panel

Please download the detailed controller manual



## AUTOMATIC SHUTDOWN AND FAULT CONDITIONS

- Under/over speed; fail to start
- High engine temperature; fail to stop
- Low oil pressure; charge fail
- Under/over generator volts; over current
- Under/over generator frequency; emergency stop
- Under/over mains frequency
- Under/over mains voltage
- Low/high battery volts

## CHNIT MCCB breaker 3P



## Sealed 12/24V Dry battery





ATS



Remote Control



Charger



Jacket Heater



Oil Heater



Extra Fuel Tank



Parallel Cabinet



Trailer



Contact Information

Email: [sale5@fjepos.com](mailto:sale5@fjepos.com)

Phone: +86 19890349907

WHATSAPP



WECHAT



VIBER

