

# EM8000

## Gasoline Generator

EMEAN  
POWER

### TECHNICALS SPECIFICATIONS

Model:

**EM8000**

Gen set composed of engine and alternator perfectly assembled and fitted in a practical tubular chasis, that is adding great strenght and versatility.

### Genset General Characteristics

|                     |  |            |
|---------------------|--|------------|
| Prime Power:        | 50HZ/7KW   | 60HZ/7.5KW |
| Standby power:      | 50HZ/7.5KW   | 60HZ/8KW   |
| DC Output:          | 12V-8.3A   |            |
| Voltage:            | 110V/220V、115V/230V、<br>120V/240V、127V/220V、<br>220V/380V、230/400V、<br>240V/415V |            |
| Fuel Tank Capacity: | 25L  |            |
| Fuel Consumption:   | ≤2.55L/h / ≤2.75L/h  |            |
| Noise Level at 7M:  | 69~71dB(A)   |            |
| Product Dimensions: | 675*525*540 MM   |            |
| Packing Dimension   | 690*540*560 MM   |            |
| N.W/G.W:            | 83KG/88KG  |            |

### OPTIONS

- Electric Start
- ATS
- Digital Meter
- Handles & Wheels
- Socket Style



### Engine

|                    |   |
|--------------------|---|
| Model:             | 192F  |
| Fuel:              | Gasoline                                    |
| Cooling System:    | Air   |
| Type:              | V-twin/L-single、4-cycle                     |
| Bore x Stroke:     | 92*66MM                                     |
| Displacement:      | 0.442L                                      |
| Compression Ratio: | 20:01                                       |
| Engine Speed:      | 50HZ/3000RPM<br>60HZ/3600RPM                |
| Rated Output:      | 50HZ/8.1KW<br>60HZ/8.7KW                    |
| Combustion System: | Crystal Ignition                            |
| Starting System:   | Recoil Start /<br>Electric Start            |
| Lube Oil Capacity: | 1.1L  |
| Lubrication Oil:   | CD Grade Or Higher<br>(SAE10W/30/SAE15W/40) |

### Alternator

|                    |   |
|--------------------|---|
| Type:              | Self Excitation、Constant<br>Voltage、Field Rotating、<br>2 Pole |
| Phase:             | Single Phase/3-Phase  |
| Power Factor:      | cOsφ 1.0/0.8  |
| Insulation:        | H   |
| Portection Degree: | IP21  |

EMEAN POWER

www.emeanpower.com  
Email: sale5@fjepos.com  
Phone: +86 19890349907

WHATSAPP



WECHAT

